

UNDERGROUND CABLE LAYING ACCESSORIES

CABLE PULLING SOCK HEAD TYPE



MODEL	Cable	Standard length	Version "L" length	Standard length weight	Version "L" weight	Breaking load
	Ø mm	mm	mm	kg	kg	kN
CT 13	10 – 15	600	900	0,100	0,220	20
CT 14	15 – 20	600	900	0,180	0,250	20
CT 15	20 – 25	600	1000	0,250	0,450	25
CT 16	25 – 30	600	1200	0,270	0,500	30
CT 17	30 – 40	700	1500	0,300	0,550	45
CT 18	25 – 45	700	1500	0,350	0,600	50
CT 19	40 – 50	800	1500	0,600	1,200	50
CT 20	45 – 60	800	1600	0,700	1,250	50
CT 21	60 – 80	800	1800	0,900	1,800	80
CT 22	80 – 100	1000	2000	1,000	1,900	100
CT 23	100 – 140	1200	2000	1,100	2,000	100
CT 24	140 – 170	1200	2000	1,700	2,800	100
CT 25	170 – 200	1200	2000	2,200	3,500	100

NOTE:

- "Long" version code CT...L
- Thimble eye version code CT...R

CABLE PULLING SOCK DOUBLE HEAD TYPE



MODEL	Cable	Total length	Weight	Breaking load
	Ø mm	mm	kg	kN
CT 26	10 – 15	1200	0,180	20
CT 27	15 – 20	1200	0,300	20
CT 28	20 – 25	1200	0,450	25
CT 29	25 – 30	1200	0,500	30
CT 30	30 – 40	1400	0,550	45
CT 31	25 – 45	1400	0,600	50
CT 32	40 – 50	1600	1,200	50
CT 33	45 – 60	1600	1,250	50
CT 34	60 – 80	1600	1,700	80
CT 35	80 – 100	2000	1,850	100
CT 36	100 – 140	2400	2,000	100
CT 37	140 – 170	2400	3,000	100
CT 38	170 – 200	2400	4,000	100



CABLE PULLING SOCK DOUBLE EYE OPEN TYPE



MODEL	Cable	Total length	Weight	Breaking load
	Ø mm	mm	kg	kN
CT 39	10 - 15	800	0,200	20
CT 40	15 - 20	800	0,230	20
CT 41	20 - 25	800	0,350	25
CT 42	25 - 30	800	0,400	30
CT 43	30 - 40	1000	0,450	45
CT 44	25 - 45	1000	0,500	50
CT 45	40 - 50	1000	0,800	50
CT 46	45 - 60	1000	0,950	50
CT 47	60 - 80	1000	1,100	80
CT 48	80 - 100	1200	1,300	100
CT 49	100 - 140	1400	1,700	100
CT 50	140 - 170	1400	2,100	100
CT 51	170 - 200	1400	2,800	100

CABLE PULLING SOCK DOUBLE EYE OPEN TYPE WITH LATERAL OPENING



MODEL	Cable	Total length	Weight	Breaking load
	Ø mm	mm	kg	kN
CT 52	10 - 15	800	0,200	20
CT 53	15 - 20	800	0,230	20
CT 54	20 - 25	800	0,350	25
CT 55	25 - 30	800	0,400	30
CT 56	30 - 40	1000	0,450	45
CT 57	25 - 45	1000	0,500	50
CT 58	40 - 50	1000	0,800	50
CT 59	45 - 60	1000	0,950	50
CT 60	60 - 80	1000	1,100	80
CT 61	80 - 100	1200	1,300	100
CT 62	100 - 140	1400	1,700	100
CT 63	140 - 170	1400	2,100	100
CT 64	170 - 200	1400	2,800	100